Kahlo Pendant Light Range

Surface & Pendant Series



FEATURES

- Variable Height & Pendant Drop Sizes
- Die-cast Aluminium housing
- Optional Pendant Accessory for Suspension option
- IP20 for Indoor application
- Ripple free dimming prevents visible flickering
- Integral DALI Drivers
- High efficiency CREE LED chip

tunable | 60 Martin Place / Sydney NSW 2000 Australia
T +612 9127 7736 | **E** info@tunable.au | **tunable.au**

Kahlo Pendant Light Range

Surface & Pendant Series

LUMINAIRE SPECIFICATION

SKU	DIAMETER	WATTAGE
TN-KAHLO-X	Ø 76mm	7W - 15W
Colour Temperature	3000K, 4000K, 2700K-6000K	
Beam Angle	 24° 36°	
IP Rating	IP20	
Fitting Colour	White, Black	
Dimmable	DALI	
Light Source Brand	CREE LED	
Efficiency (lm/w)	100lm/w	
CRI	80	

ORDER INFORMATION

	Output	Beam	CT	Colour
TN-KAHLO	7W 10W 12W 15W	24° 36°	3000K 4000K Tunable	White Black

TECHNICAL SPECIFICATION

Driver Supplied	BOKE
Rated Voltage	220-240VAC 50-60Hz
Working Temp	25 ~ +60℃
in Rush Current	5A 50μs
Thermal Protection	C.5.a.
Body Material	Aluminium



Variable Height
150mm - 1000mm

Ø 76mm

STANDARDS COMPLIANCE

EN61347-1 • EN61347-2-13 • EN62384
EN55015 • EN61000-3-2 • EN61000-3-3 • EN61000-4-2,3,4,5,6,8,11 • EN61547
IEC 62386-101 • IEC 62386-102 • IEC 62386-207 • IEC 62386-209
IEC 61347-2- 13 Annex J • EN 60598-2-22 • EN 50172

5 YEARS WARRANTY
5% FAILURE RATE

tunable | 60 Martin Place / Sydney NSW 2000 Australia
T +612 9127 7736 | **E** info@tunable.au | **tunable.au**