# Murus Wall Light Range

DT8 Colour Tuneable

## Wall Light Series



## FEATURES

- Screwless design with magnetic mount
- Comfortable and symmetric light performance
- Light housing: Pure aluminum
- Surface mounted and no need wall-mouted plate
- Light source: COB LED with a reflector of high optical.
- .
- .
- .


**tunable** | 60 Martin Place / Sydney NSW 2000 Australia
**T** +612 9127 7736 | **E** info@tunable.au | **tunable.au**

tunable

## Wall Light Series

### LUMINAIRE SPECIFICATION

| SKU | DIAMETER | WATTAGE |
|---|---|---|
| TN-MUR-X | Ø mm | 2x 8W |
| Colour Temperature | 3000K, 4000K | |
| Beam Angle |   | |
| IP Rating | IP44 | |
| Fitting Colour | White, Silver, Black | |
| Dimmable | DALI | |
| Light Source Brand | CREE LED | |
| Efficiency (lm/w) | 58lm/w | |
| CRI | 80 | |




### ORDER INFORMATION

| | Output | Beam | CT | Colour |
|---|---|---|---|---|
| TN-MUR | 2x 8W | 20°<br>40°<br>60° | 3000K<br>4000K<br>Tunable | Black |

### TECHNICAL SPECIFICATION

| | |
|---|---|
| Driver Supplied | Sunricher |
| Rated Voltage | 220-240VAC 50-60Hz |
| Working Temp | 25 ~ +60℃ |
| in Rush Current | 5A 50μs |
| Thermal Protection | C.5.a. |
| Body Material | Aluminium |

### STANDARDS COMPLIANCE

EN61347-1 • EN61347-2-13 • EN62384
EN55015 • EN61000-3-2 • EN61000-3-3 • EN61000-4-2,3,4,5,6,8,11 • EN61547
IEC 62386-101 • IEC 62386-102 • IEC 62386-207 • IEC 62386-209
IEC 61347-2- 13 Annex J • EN 60598-2-22 • EN 50172

**5**
YEARS
WARRANTY
5% FAILURE RATE

**tunable** | 60 Martin Place / Sydney NSW 2000 Australia
**T** +612 9127 7736 | **E** info@tunable.au | **tunable.au**